

Cable Drum, Tubing and Container Trailers BKT 10 up to BKT 15



Cable drum trailer type BKT 15

The special loading platform is based on the standard container with a capacity of 1.6 m³, order no. 030.101.00. The two pick-up jibs operated by a hydraulic hand pump, will swing out the platform behind the trailer.



Cable drum trailer type BKT 10 with a hydraulic power pack (4 kW) and a single arm cable drum drive for fibre optic cables.



Cable drum trailer type BKT 12/15 with extendible pick-up jibs and tube coil cage RH 160

The pick-up jibs and the cage may be adjusted to coil diameters of up to 3700 mm. After the packing straps have been removed from the coil, the tube can be uncoiled out of the centre.

Capacity: tube-dia. 90-160 mm, max. length: 100 m



Cable drum trailer BKT 15 with container 1.6 m³

The container has a capacity of 1.6 m³ and is equipped with lockable cover.

Order No. 030.101.50.

Specifications are subject without notice. Output details are depending on use conditions.

Cable Drum, Tubing and Container Trailers

BKT 10 up to BKT 15



BKT 10-12-15

The loading frame is tilted up with a non-recoiling, hand-operated windlass and secured with a bolt. Upon request, all trailers may be delivered with extensible loading jibs for picking up tube reels.



BKT 10K, BKT 12K, BKT 15K

BKT 10 K with Tube reel RH 63

The BKT 10 - 15 Trailer is loaded by two tiltable jibs with manually operated hydraulic pump and two double acting hydraulic cylinders. Upon request, all trailers may be delivered with extensible loading jibs for picking up tube reels. Larger diameters of pipe coils than mentioned for the cable drums can be transported with that additional extensions.



The trailers of both construction series are hot galvanized.

Technical Data:

| Type | Pay load kg | Empty weight kg | Total weight kg | Max. drum dia. mm | Loading width mm | -o single-straight | | -o single-height-adjustable | | | Order No. |
|------------------|----------------|--------------------|--------------------|----------------------|---------------------|--------------------|---------|-----------------------------|-------------|--------------|-------------------|
| | | | | | | Chassis | | Length mm | Width mm | Height mm | |
| | | | | | | Type | Brake | | | | |
| BKT 10 | 900 | 400 | 1300 | 1800 | 1400 | -o | overrun | 3200 | 2000 | 1600 | 008.020.00 |
| BKT 12 | 1150 | 450 | 1600 | 2000 | 1500 | -o | overrun | 3200 | 2200 | 1700 | 008.021.00 |
| BKT 15 | 1150 | 500 | 2000 | 2500 | 1600 | -o | overrun | 3400 | 2300 | 1850 | 008.022.00 |
| BKT 12/15 | 1140 | 460 | 1600 | 2500 | 1580 | -o | overrun | 3680 | 2260 | 1940 | 008.740.00 |
| BKT 10 | 900 | 400 | 1300 | 1800 | 1400 | -o | overrun | 4000 | 2000 | 1600 | 008.020.01 |
| BKT 12 | 1150 | 450 | 1600 | 2000 | 1500 | -o | overrun | 4050 | 2200 | 1700 | 008.021.01 |
| BKT 15 | 1500 | 550 | 2050 | 2500 | 1600 | -o | overrun | 4200 | 2300 | 1700 | 008.022.01 |
| BKT 10K | 950 | 350 | 1300 | 1800 | 1400 | -o | overrun | 3200 | 2000 | 1600 | 008.015.00 |
| BKT 12K | 1200 | 400 | 1600 | 2000 | 1500 | -o | overrun | 3200 | 2200 | 1850 | 008.016.00 |
| BKT 15K | 1500 | 500 | 2000 | 2500 | 1600 | -o | overrun | 3400 | 2300 | 1900 | 008.017.00 |
| BKT 10K | 950 | 350 | 1300 | 1800 | 1400 | -o | overrun | 4000 | 2000 | 1600 | 008.015.01 |
| BKT 12K | 1200 | 400 | 1600 | 2000 | 1500 | -o | overrun | 4050 | 2200 | 1850 | 008.016.01 |
| BKT 15K | 1500 | 550 | 2050 | 2500 | 1600 | -o | overrun | 4200 | 2300 | 1900 | 008.017.01 |

Specifications are subject without notice. Output details are depending on use conditions.

Bagela®