



- Lateral movable limit bar for limitation of different pipe coil width
  - The quick roller change system shortens the changeover time for 60 % and lowers the danger of accidents which is imminent by two handed screwing.
  - Depending on the bid loading width coil dimensions of up to 180 mm can be loaded
- It enables the transport of HDPE-tubing drums too.
- Simultaneous uncoiling of three pipe coils is possible (pipe dia. 100 mm, pipe coil length:100 m)

**Attention: The inner end of the pipe is to be cut. It has to be flush to the pipe coil!**

Uncoiling cages can be used also without trailer as freestanding device. Tool trailer are suitable likewise, however a safe attachment must be ensured.

The Bagela cable drum trailer of the series BKT 23 and 27 is equipped with the necessary attachment for the Uncoiling cage and are able to load and unload it independently.

In addition, the Uncoiling can be used in a cable drum trailer of strange brand.

### Technical Data:

Type	Pay load	Empty-Weight	Total weight	Max. dia. pipe coil	Loading width	Chassis		Length mm	Width mm	Height mm	Order No..
						Type	Brake				
BRVT 17	1700 kg	1300 kg	3000 kg	3700 mm	1720 mm	-oo	overrun	5800	2520	1230	038.700.00
BRVT 17	1800 kg	1200 kg	3000 kg	3700 mm	1720 mm	-oo	overrun	5300	2520	1250	038.700.10
Uncoil. cage		450 kg		1490 mm				3800	1975	2655	008.331.00
Uncoil. cage wide		580 kg		1720 mm				3800	2205	2655	008.331.01

Specifications are subject without notice. Output details are depending on use conditions.